

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
21 July 2005 (21.07.2005)

PCT

(10) International Publication Number  
**WO 2005/065275 A2**

(51) International Patent Classification: **Not classified**

(21) International Application Number:  
PCT/US2004/043428

(22) International Filing Date:  
23 December 2004 (23.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/532,847 24 December 2003 (24.12.2003) US

(71) Applicant (for all designated States except US): **BAR-  
RETT TECHNOLOGY, INC.** [US/US]; 625 Mount  
Auburn Street, Cambridge, MA 02138 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **TOWNSEND,**

**William, T.** [US/US]; 31 Country Drive, Weston, MA  
02493 (US).


(74) Agents: **MANUS, Peter, J.** et al.; Edwards & Angell, LLP,  
P.O. Box 55874, Boston, MA 02205 (US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: AUTOMATIC PRETENSIONING MECHANISM FOR TENSION-ELEMENT DRIVES



(57) Abstract: A mechanism for pretensioning a cable, or like tension element, of a tension-element drive selectively engages the motor drives of the cable for pretensioning. The mechanism uses a sleeve on which a portion of the cable is wound, with another portion of the cable wound in an opposed direction on a drive shaft on the motor. A clutch connects the sleeve to the motor output shaft. An initiator mechanism selectively stops rotation of the sleeve and the cable portion wound on the sleeve while allowing the motor torque to act on the other end of the cable wound on the drive shaft.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *without international search report and to be republished upon receipt of that report*